



# #16 High Pressure Hydraulic Hose

**Tried. Tested. And Wanted.**

## PRODUCT DESCRIPTION

### APPLICATIONS

Used on high pressure hydraulic systems which require Nylon Tubes.

### TEMPERATURE

-40°F to 200°F

### INNER TUBE

Polyamide or Polyester Elastomer (Dupon)

### REINFORCEMENT

One braid of Polyester fiber.

### COVER

Black abrasion resistant Polyurethane.

## ORDER & PACKAGING

### PLACING AN ORDER OR REQUEST

Specifying Standard Items:

Please specify the following:

1. Series(Item) Number
2. OD. Size
3. ID. Size
4. Tube length (Please specify Metric/Imperial)
5. Color

#### *Example of a request*

330ft of 0.32" x 1/8 " Black High Pressure Hydraulic Hose

HPH 32 18 330FT BK

• Series

• OD

• ID

• Length

• Color

## HIGH PRESSURE HYDRAULIC HOSE

### Series

HPH

### Working Pressure

4 to 1 safety factor

### Temperature Range

-40°C ~ 90°C

-40°F ~ 194°F

### Standard color

BK. Black / R. Red / BU. Blue

### METRIC SIZE

LTEM NO.	HOSE SIZE		MAX. WORKING PRESSURE AT 75°F (psi)	MIN. BURST PRESSURE AT 75°F (psi)	LENGTH (ft)
	OD (inch)	ID (inch)			
HPH200B10	.32"	1/8"	3000	12000	330.600
HPH200B15	.45"	3/6"	3000	12000	330.600
HPH200B20	.50"	1/4"	2750	11000	330.600
HPH200B25	.58"	5/16"	2500	10000	330
HPH200B30	.67"	3/8"	2250	9000	330
HPH200B40	.82"	1/2"	2000	8000	330

\* Other sizes, colors, printing, length and package option may be available

### PACKAGING

#### TYPE

#### FEATURE



#### **Paper Reel**

100M or 200M  
0 splices allowed

An easy to use standard package.



#### **Film Wrapped**

0 splices allowed

A package for special lengths and large-scaled O.D that can be recycled.



